



VINEYARD MOWERS

Trusted by vignerons for over 35 years!



GASON[®]

GASON VINEYARD MOWERS

The Gason range of Vineyard Mowers has been a long time favourite of Australian and New Zealand viticulturists for over 35 years. Pioneered by Chris Grow Engineering, our products have been used extensively in many of the leading vineyards around the world - most notably the USA and Europe.

Gason Twin Rotor Rapier Mowers offer all the functionality requirements for current Viticultural industry practice. Added safety guarding ensures worksafe requirements are maintained, and all mowers are fitted with premium Comer Italian gearboxes*, PTO shafts and clutches. All cutterhead gearboxes include underbody extension housings for strong output shaft support.

Our Vineyard Mowers trim the inter-row sward of permanent Sod or Cover Crop and discharges each side under vine to suppress weed growth and retain soil moisture. Optional shredder kit finely mulches prunings and spreads evenly behind the mower. Fully adjustable cutting height control is consistently maintained via domed end rear rollers or wheels.



Notes:

Vineyard Mower Specifications

Deck Size	Front Mount	Rear Mount	Drop Centre	Single Rotor	Twin Rotor	Cutting Width	Approx. Weight
5' 3"		✓		✓		1.55m	595kg
5' 11"	✓	✓			✓	1.80m	900kg
6' 0"		✓			✓	1.80m	840kg
6' 2"		✓	✓		✓	1.80m	980kg
6' 6"		✓	✓		✓	1.94m	850kg*
7' 2"		✓	✓		✓	2.08m	1000kg
7' 4"	✓	✓			✓	2.14m	1096kg*
8' 0"		✓			✓	2.34m	1120kg

Models	Cutting Width & Weight
6'	1.81m ~800kg
6' 6"	1.94m ~850kg
7' 4"	2.14m ~1096m
8' 0"	2.34m ~1120kg

Standard Features	
Deck Materials	Angular streamline 6mm deck with underside reinforced
Gearbox	Comer 3 gearbox *BareCo gearbox fitted to 5' 3" Single Rotor
Clutch	4 plate clutch
Skids	Full 6mm sides including hardened steel skids
Rotor Bar	Laminated spring steel bars
Blades	Suction uplift swing back blades
Linkage Mounting	Cat 2 – 3PL
Front & Rear Chains	Galvanised safety chains

Options	(model dependent)
Single Blade	SB
Dual Blade	DB
Rear Wheel Kit	RWK
Rear Roller	RR
Front Roller	FR

Additional Information
 Suitable for 45 – 100HP tractors
 PTO 540rpm

